

# HPM4000

## Hydraulic data logger - SR

The HPM4000 is the ideal entry level product for hydraulic fault prevention and diagnostics. It enables a service engineer to connect either two or three sensors simultaneously, depending on the display, data log and export results to HPMComm for further analysis. HPMComm is Windows compatible software that is included free-of-charge with all Webtec HPM devices.

The HPM4000 not only allows the user to display actual values, like flow, pressure and temperature but also display peak pressure, and calculate values such as differential pressure and hydraulic power.

The rugged handheld unit combines a 3 1/2" square backlit LCD with powerful data logging functionality, 1GB of memory on a nano-USB stick and full device/host USB compatibility.

### Specifications

<b>Operating Temperature Range:</b>	0 to 50°C, 32 to 122°F
<b>Power Supply:</b>	Input 100 - 240 VAC
<b>Connection Type:</b>	Micro-USB socket, Type B, +5 VDC max 1000mA
<b>Battery:</b>	Lithium Ion pack 3.7 VDC, 2250 mAh
<b>Battery life:</b>	With 2 sensors >8 hours
<b>Degree of Protection:</b>	IP54 (EN60529)
<b>Housing Material:</b>	ABS/PC
<b>Housing Protective Shield:</b>	TPU
<b>Weight:</b>	0.54 kg, 1.19 lb

Make it **BLUE**

### Features

- Complete range of sensors – pressure, flow, temperature, tachometer.
- Analogue SR sensors with sensor recognition.
- Large 3.5" back-lit display for quick and easy readings.



## Sales Order Code

Please contact our technical sales team to discuss any special order requirements.

MODEL NUMBER	INPUTS (NUMBER AND TYPE OF SENSORS)
SR-HPM-4020-05-0C	2 'SR' sensors – up to four channels

### Notes

USB Power Supply (5V, 1A) and USB Cable are included in delivery.

Some sensors, such as the PTT pressure transducers that include a temperature sensor built-in, are one sensor that uses two channels.

## Memory

Internal memory: 1 measurement – approx. 15,000 data records  
 USB memory stick: 1GB supplied – supports up to 4GB

## Interface

USB device: Online data transfer between device and PC via HPMcomm software; measured value transfer: ACT/MIN/MAX, min. 5 ms; USB standard: 2.0, full speed; connection assembly: Micro USB socket, protected, type B.  
 USB host: Connection of USB memory stick, max. 4 GB; recommended types: Delock USB 2.0 Nano memory stick, Intenso Micro Line; USB standard: 2.0, full speed, max. 100 mA; connection assembly: Micro USB socket, protected, type B.

## Display

Type: FSTN-LCD, graphical, with LED background lighting  
 Visible area: 62 x 62 mm, 2.4 x 2.4 Inches  
 Resolution: 130 x 130 pixels

## HPM4000 Dimension

W x H x D: 96 x 172 x 54 mm, 3.8 x 6.8 x 2 Inches